

Slim, Sleek, Smooth



Picture and logos

SELLING POINTS

- Goditi un intrattenimento di alta qualità con una frequenza di aggiornamento di 100Hz per un'esperienza più fluida.
- Il display certificato TÜV garantisce la protezione e la salute degli occhi.
- La tecnologia MSI EyesErgo con tecnologia Anti-Flicker aiuta a prevenire affaticamento e tensione degli occhi.
- MSI Eye-Q Check ti aiuta a fare un'autocontrollo degli occhi e ti ricorda di fare una pausa quando usi il monitor per lungo tempo.
- Mantieni la versatilità su diversi dispositivi utilizzando fonti di ingresso multiple, come HDMI™ e DisplayPort.
- Goditi un ambiente più pulito con un design conveniente e rimovibile per la gestione dei cavi.
- La tecnologia HDR produce immagini con maggiori dettagli.



1. 5-way Navigator
2. 1x DC Jack
3. 1x Headphone-out
4. 1x DisplayPort 1.2a
5. 1x HDMI™ 1.4b (FHD@100Hz)
6. Kensington Lock



BUSINESS PRODUCTIVITY MONITOR

PRO MP242L

PRO MP242L

SPECIFICATION

| | | |
|-----------|---|--------------------------------|
| Model | Part No | 9S6-3PD5CT-015 |
| | Color | ID1/Black-Black |
| Display | Screen Size | 23.8" (60.45cm) |
| | Active Display Area (mm) | 527.04(H) x 296.46(V) |
| | Curvature | Flat |
| | Panel Type | IPS |
| | Resolution | 1920x1080 (FHD) |
| | Pixel pitch (mm) | 0.2745(H)x0.2745(V) |
| | Aspect Ratio | 16:9 |
| | Dynamic Refresh Rate technology | Adaptive-Sync |
| | Dynamic Refresh Rate Activated Range | 48~100Hz |
| | HDR (High dynamic range) | HDR Ready |
| | SDR Brightness (nits) | 250 |
| | Contrast Ratio | 1000:1 |
| | DCR (Dynamic Contrast Ratio) | 100000000:1 |
| | Signal Frequency | 52.8~110 KHz(H) / 48~100 Hz(V) |
| | Refresh Rate | 100HZ |
| | Response Time (MPRT) | 1ms(MPRT) |
| | Response Time (GTG) | 4ms |
| | View Angles | 178°(H)/178°(V) |
| | NTSC (CIE1976 area percentage/overlap) | 91%/79% |
| | NTSC (CIE1931 area percentage/overlap) | 72%/69% |
| | SRGB (CIE1976 area percentage/overlap) | 104%/97% |
| | SRGB (CIE1931 area percentage/overlap) | 102%/95% |
| | Adobe RGB (CIE1976 area percentage/overlap) | 89%/85% |
| | Adobe RGB (CIE1931 area percentage/overlap) | 76%/73% |
| | DCI-P3 (CIE1976 area percentage/overlap) | 83%/83% |
| | DCI-P3 (CIE1931 area percentage/overlap) | 75%/75% |
| | Rec.709 (CIE1976 area percentage/overlap) | 104%/97% |
| | Rec.709 (CIE1931 area percentage/overlap) | 102%/95% |
| | Rec.2020 (CIE1976 area percentage/overlap) | 60%/60% |
| | Rec.2020 (CIE1931 area percentage/overlap) | 54%/54% |
| | Surface Treatment | Anti-glare |
| | Display Colors | 16.7M |
| | Color bit | 8 bits (6 bits + FRC) |
| I/O Ports | Headphone-out | 1 |
| | Lock type | Kensington Lock |
| | HDMI | 1 |
| | HDMI version | 1.4b |
| | HDMI HDCP version | 1.4 |
| | DisplayPort | 1 |
| | DisplayPort version | 1.2a |
| | DisplayPort HDCP version | 1.3 |
| Warranty | Warranty | 24M |
| Power | Power Type | External Adaptor 12V 2A |
| | Power Input | 100~240V, 50/60Hz |
| | On-mode Power Consumption (KWh/1000h) | 14 (SDR) 30 (HDR) |
| | Annual Energy Consumption (KWh) | 27 |
| | Standby-mode Power Consumption (W) | 0.5 |
| | Off-mode Power Consumption (W) | 0.3 |
| | Energy Efficiency Rating | D (SDR) G (HDR) |



BUSINESS PRODUCTIVITY MONITOR

PRO MP242L

PRO MP242L

| | | |
|------------------------------|--|--------------------|
| In The Box | DisplayPort Cable | 0 |
| | HDMI Cable | 1 |
| | DVI Cable | 0 |
| | USB Type A to Type B Cable | 0 |
| | USB Type C to Type A Cable | 0 |
| | USB Type C to Type C Cable | 0 |
| | Thunderbolt Cable | 0 |
| | VGA Cable | 0 |
| | 3.5mm audio Cable | 0 |
| | 3.5mm combo audio Cable | 0 |
| | 3.5mm Mic Cable | 0 |
| | Power Cord | 0 |
| | AC Adaptor | 1 |
| | Quick Guide | 1 |
| | Warranty Card | 0 |
| | Mouse Bungee Unit | 0 |
| Design | Adjustment (Tilt) | -3.5° ~ 21.5° |
| Dimension & Weight (product) | Product Dimension with Stand (WxDxH) (mm) | 542 x 174 x 391 |
| | Product Dimension without Stand (WxDxH) (mm) | 542 x 28 x 321 |
| | Stand Dimension (WxDxH) (mm) | 174 x 174 x 111 |
| | Weight (Net kg) | 1.8 |
| Dimension & Weight (box) | Weight Without Stand (kg) | 1.6 |
| | Inside Carton Dimension (WxDxH) (cm) | 60 x 11.1 x 40 |
| | Outer Carton Dimension (WxDxH) (cm) | 61.5 x 12.6 x 42.3 |
| Barcode Info | EAN | 4711377258968 |